

## Studlink Chain – Grade 3

Available Galvanised or Black – Larger sizes available on request.



Dia. ['d'] (mm)	Grade 3		Weight kg/ 27.5m	Weight kg/m
	Proof Load (tonne-f)	Break Load (tonne-f)		
12.5	9.4	13.5	11	4.0
14	11.8	16.8	130	4.7
16	15.3	22.0	170	6.2
17.5	18.3	26.1	180	6.5
19	21.5	30.7	220	8.0
20.5	24.9	35.6	260	9.4
22	28.6	40.9	300	10.9
24	33.9	48.5	340	12.4
26	39.7	56.7	405	14.7
28	45.8	65.5	475	17.3
30	52.4	74.9	545	19.8
32	59.4	84.9	615	22.4
34	66.8	95.5	690	25.1
36	74.6	107.0	775	28.2
38	82.8	118.0	760	31.3
40	91.4	131.0	950	34.5
42	100.0	143.0	1040	37.8
44	110.0	157.0	1130	41.1
46	119.0	171.0	1240	45.1
48	130.0	185.0	1345	48.9
50	140.0	200.0	1455	52.9
52	151.0	215.0	1575	57.3
54	162.0	231.0	1690	61.4
56	174.0	248.0	1810	65.8
58	185.0	265.0	1945	70.7
60	198.0	282.0	2075	75.4
62	210.0	300.0	2220	80.7

Dia. ['d'] (mm)	Grade 3		Weight kg/ 27.5m	Weight kg/m
	Proof Load (tonne-f)	Break Load (tonne-f)		
64	223.0	319.0	2370	86.2
66	236.0	337.0	2525	91.8
68	250.0	357.0	2685	97.6
70	263.0	376.0	2850	103.6
73	285.0	407.0	3100	112.7
76	307.0	438.0	3360	122.2
78	322.0	459.0	3535	128.5
81	345.0	492.0	3820	138.9
84	368.0	526.0	4105	149.3
87	393.0	561.0	4405	160.2
90	417.0	596.0	4705	171.1
92	434.0	620.0	4905	178.4
94	460.0	657.0	5210	189.4
97	477.0	682.0	5425	197.3
100	504.0	720.0	5745	208.9
102	522.0	746.0	5970	217.1
105	550.0	785.0	6320	229.8
107	568.0	812.0	6575	239.1
111	606.0	865.0	7080	257.4
114	635.0	907.0	7475	271.8
117	664.0	948.0	7870	286.2
120	694.0	991.0	8270	300.7
122	714.0	1019.0	8550	310.9
124	734.0	1048.0	8835	321.3
127	764.0	1092.0	9270	337.1
130	795.0	1136.0	9710	353.1
132	816.0	1165.0	10005	363.8

